



STOP CREVAISON

Tire sealant

USES

YACCO Tire sealant 500 ml spray can is easy and fast to use. It repairs and inflates all types of tires, including tubeless ones (do not use in Run flat tires).

It is suitable for all vehicles equipped with tires up to 225 mm : cars, light commercial vehicles, SUVs, 4x4s, campers, trailers...

MAIN PHYSICAL DATA

	Method	Units	Values
Appearance	Visual		Liquid
Couleur	Visual		White
Density at 20°C	ASTM D4052	kg/m3	1000
pH	ASTM D92		9.3

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Quick and easy to use.
- ▶ It avoids to remove the wheel at the side of the road and getting hands dirty.
- ▶ A 500 ml allows repair of large size tires

INSTRUCTIONS FOR USE

- ▶ Make sure that you are not on the unsafe side of the road.
- ▶ Make sure the tire is not off the rim or torn. Remove the object that has caused the puncture.
- ▶ Move the car until the valve of the wheel reaches the upper position.
- ▶ Shake well before use. In case of cold outside temperature, warm the can up in your hands.
- ▶ Attach the hose to the tire valve stem.
- ▶ Hold the trigger down until no more product flows in.
- ▶ Get the vehicle back on the road and drive away at low speed (max 40 km/h) during few kilometers to allow the product to coat the inside of the tire. Add air to top up the pressure to the required amount.
- ▶ Drive at moderate speed (max 80 km/h) and get as soon as possible to a nearby garage for a permanent repair.

PRECAUTIONS FOR USE

- ▶ Seals punctures up to 5 mm. Do not use on sidewall punctures.
- ▶ Before use, carefully read the safety information on the label of the product and check the instructions given on the Health and Safety Data Sheet available at yacco.com.

YACCO LINE



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

