



Graisse HP

Molybdenum disulphide extreme-pressure grease

USES

Especially recommended for use in severe service conditions, YACCO HP grease provides exceptionally long-lasting lubrication.

Suitable for equipment exposed to poor weather conditions and subjected to heavy loads, such as lorries, construction equipment and agricultural equipment, etc.

SPECIFICATIONS

NLGI Grade 2

ISO 6743-9 → ISO-L-XBCHB 2

DIN 51502 → DIN GP2N-25

MAIN PHYSICAL DATA

	METHOD	Values
Colour	Visual	Black
Appearance	Visual	Smooth
Consistency (penetration 60 strokes)	ISO 2137	275 (10 ⁻¹ mm)
Drop point	ISO 2176	192°C
Thickener		Lithium Calcium
Welding load	ASTM D2596	315kg

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ High quality colloidal suspension of micronized molybdenum disulphide to optimize anti-wear and greasing properties under limited conditions.
- ▶ Excellent extreme-pressure property,
- ▶ Water insoluble.
- ▶ Effective over a wide temperature range: -20°C to +130°C (140°C max. temperature).

YACCO LINE



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

