



EMBASE RACING SAE 75W-90

100% synthetic oil for highly-stressed gear cases

USES

High performance, anti-emulsion gear case oil specifically developed for the lubrication of propeller cases on outboard racing engines. Change oil for every race.

Specifications:

API GL-5 & API GL-4

MAIN PHYSICAL DATA

| | | Methods | Units | Values |
|------------------------|-------|------------|--------------------|--------|
| Density at | 20°C | ASTM D4052 | kg/m ³ | 865 |
| Kinematic viscosity at | 40°C | ASTM D445 | mm ² /s | 110 |
| Kinematic viscosity at | 100°C | ASTM D445 | mm ² /s | 16 |
| Viscosity index | | ASTM D2270 | | 156 |
| Pour point | | ASTM D97 | °C | -57 |

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Outstanding extreme-pressure properties.
- ▶ Exceptional anti-emulsion properties, allowing fast water/oil separation in the event of water getting into the oil.
- ▶ Very high shear stability maintains optimal oil viscosity in service.
- ▶ Increased protection against corrosion.
- ▶ Full synthetic SAE 75W90 formula ensures excellent lubrication at all temperatures.
- ▶ Good anti-wear and anti-foam properties extend the engine's service life.



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

