



VX 1500 - SAE 0W-30

100% synthetic fuel economy oil for high performance gasoline and diesel engines

USES

100% synthetic fuel economy engine oil for passenger cars. Reduces exhaust emissions. Suitable for gasoline and diesel engines, including those fitted with direct injection systems and turbochargers.

Particularly recommended where the manufacturer specifies the use of SAE 0W-30 ACEA A5/B5, ACEA A5/B5, API SL or VOLVO VCC 95200377 oil: Volvo, Toyota, Mitsubishi, Honda, etc.

Approval: VOLVO VCC 95200377

Specifications: ACEA A5/B5: API SL



MAIN PHYSICAL DATA

		Methods	Units	0W-30
Density at	20°C	ASTM D4052	kg/m ³	842
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	53
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	10
Viscosity index		ASTM D2270		179
Pour point		ASTM D97	°C	-42
Cleveland Open Cup Flash Point		ASTM D92	°C	226
Dynamic viscosity at	-35°C	ASTM D5293	mPa·s	6000
HTHS viscosity (150 °C)		CEC L-036-90	mPa·s	3.0
Sulphated ash		ASTM D874	% mass	1.1
Total Base Number (TBN)		ASTM D2896	mgKOH/g	10

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ 100% synthetic formula provides outstanding thermal resistance and excellent lubrication in any driving conditions: roads, motorways, city traffic, etc. Allows for extended oil change intervals.
- ▶ Low HTHS viscosity at 150°C (low viscosity at high temperatures and under high shear) improves fuel economy and reduces emissions, thus helping to protect the environment.
- ▶ Low viscosity in cold conditions (100% synthetic SAE 0W-30 oil) means instant oil flow for increased engine protection against wear.
- ▶ Excellent detergent/dispersant properties keep the engine clean, even under severe driving conditions.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

