



# OUTBOARD 100 2T

Mineral oil for 2-stroke outboard motors and jet-ski engines.

## USES

Mineral engine oil specifically developed for water-cooled 2-stroke outboard motors and jet-ski engines.

Oil mixing: from 1 to 3 % (depending on the OEM recommendation).

Blue colored oil for easy detection in fuel mix.

### Specifications:

NMMA TC-W3

## MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	869
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	36
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	6.5
Viscosity index		ASTM D2270		128
Pour point		ASTM D97	°C	-30
Cleveland Open Cup Flash Point		ASTM D92	°C	107
Colour			Visual	Blue
Sulphated ash		ASTM D874	% mass	No ash

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Ashless formula keeps the combustion chamber clean and prevents deposits.
- ▶ Pre-diluted formula to enhance fuel/oil miscibility.
- ▶ Increased lubrication and anti-wear properties.
- ▶ Prevents blocked exhaust ports, piston seizure and spark plug fouling.
- ▶ Excellent engine protection against seized or gummed piston rings.
- ▶ Dyed blue to allow easy detection in oil/fuel mixture.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

