



YACCO MAS3

Detergent monograde oil

USES

YACCO MAS3 SAE 30 is a mineral oil with well-proven performance additives providing outstanding lubrication and detergency. Suitable for gasoline and diesel engines (including supercharged ones) under non-severe service conditions.

Can also be used for the lubrication of gearboxes, torque converters, and hydraulic systems where the manufacturer recommends the use of SAE 30 engine oil.

YACCO MAS3 SAE 30 has a wide range of uses including agriculture, garden, marine, transport and construction sectors, etc.

Specifications:

API SF/CF
Caterpillar TO-2
Mercedes-Benz MB 228.0

MAIN PHYSICAL DATA

		Methods	Units	SAE 30
Density at	20°C	ASTM D4052	kg/m ³	891
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	104
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	11.5
Viscosity index		ASTM D2270		100
Pour point		ASTM D97	°C	-21
Cleveland Open Cup Flash Point		ASTM D92	°C	240
HTHS viscosity		CEC L-036-90	mPa·s	3.8
Sulphated ash		ASTM D874	mPa·s	1.5
Total Base Number (T.B.N)		ASTM D896	mgKOH/g	11

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Excellent detergent/dispersant properties keep the engine clean.
- ▶ Enhanced anti-wear, anti-oxidation, and anti-corrosion properties for optimal protection of the engine or transmissions.
- ▶ Enhanced shear resistance for increased viscosity stability in service.
- ▶ Good anti-foam properties provide enhanced lubrication
- ▶ Excellent anti-rust protection.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

