



# INBOARD 1000 4T SAE 5W40

100% synthetic oil for 4-stroke  
gasoline inboard engines

## USES

100% synthetic oil for 4-stroke gasoline inboard engines which run under severe or regular service conditions.

Suitable for use in 4-stroke engines from CHRIS-CRAFT, RIVA, etc.

### Specifications:

ACEA A3/B4

API SL/CF

## MAIN PHYSICAL DATA

	Méthode	Unités	Valeurs
Density at 20°C	ASTM D 4052	kg/m <sup>3</sup>	850
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	92
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15
Viscosity index	ASTM D 2270		172
Cleveland Open Cup Flash Point	ASTM D 92	°C	223
Dynamic viscosity at -30°C	ASTM D 5293	mPa.s	5800
Viscosité H.T.H.S. à 150°C	CEC L-036-90	mPa.s	4.0
Sulphated ash	ASTM D874	% masse	1.3
Total Base Number (T.B.N.)	ASTM D 2896	mgKOH/g	10,5

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Synthetic formula for increased oil stability at high temperatures.
- ▶ Very good detergent/dispersant properties keep engines clean, even under the most severe service conditions.
- ▶ Extends the engine's service life.
- ▶ SAE 5W viscosity at cold start provides quick oil flow upon start-up, whatever the temperature.

