



# MULTI 2T

Mineral oil for 2-stroke engines

## USES

Mineral oil for 2-stroke engines, such as mopeds.

Suitable for oil injector systems and premix.

Premix ratio: 3% to 6%, depending on the manufacturer's requirements.

## Specifications:

API TB

JASO FA



## MAIN PHYSICAL DATA

	Methods	Units	Values
Density at 20°C	ASTM D4052	kg/m <sup>3</sup>	880
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	73
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.2
Viscosity index	ASTM D2270		101
Pour point	ASTM D97	°C	-21
Cleveland Open Cup Flash Point	ASTM D92	°C	110
Colour			Blue

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Ensures good piston-ring sealing.
- ▶ Protects the engine against corrosion
- ▶ Excellent protection against wear.
- ▶ Dyed blue for easy detection in gasoline/oil mixture.
- ▶ Pre-diluted for easier mixing with gasoline.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

