



# Liquide Hydraulique Mineral

Mineral hydraulic fluid

## USES

Product suitable for all hydraulic and brake systems where a **mineral hydraulic liquid** is required by the OEM, i.e. hydraulic parts of **CITROËN** models.

It can also be used with industrial hydraulic systems where the manufacturer recommends this type of fluid.

**Specification** : PSA B71 2710

## MAIN PHYSICAL DATA

	Methods	Units	Values
Density at 20°C	ASTM D405	kg/m <sup>3</sup>	833
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	18.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.2
Viscosity index	ASTM D2270		340
Pour point	ASTM D97	°C	-60
Cleveland open cup flash point	ASTM D92	°C	125
Color			Green

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Outstanding stability.
- ▶ Excellent lubricating power.
- ▶ Not sensitive to moisture (non-hygroscopic product).
- ▶ Compatible with all seals materials
- ▶ Very low pour point.

## PRECAUTIONS FOR USE

**Do not use in brake systems** where a synthetic brake fluid is recommended.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

