



# AQUA GREASE

Water-insoluble lithium/calcium grease

## USES

Extreme-pressure grease totally insoluble in water. Its tacky consistency and strong adhesion mean it can be used for many different types of equipment, including marine, gardening, agricultural, construction, transportation and industrial equipment.

Especially recommended for equipment running in water or mud which is exposed to the elements, dust or corrosive environments (recreational or professional marine equipment, port facilities, construction equipment, agricultural and gardening equipment, etc.)

### Specifications:

**Grade NLGI 2**

**Temperature range: -20°C/+140°C**

## MAIN PHYSICAL DATA

|   | Values                |
|---|-----------------------|
| Colour                                    | Amber                 |
| Dropping point                            | >180°C                |
| Thickener                                 | Lithium/calcium       |
| 4 Ball EP Weld load                       | 250kg                 |
| Base oil viscosity at 40°C                | 250mm <sup>2</sup> /s |
| EMCOR test with distilled water/saltwater | 0/0                   |
| Salt spray test (EN 50326)                | No corrosion          |

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Excellent protection against corrosion. Ideal for marine equipment (fittings) exposed to seawater and sea spray.
- ▶ Long life grease with excellent adhesion and tacky consistency for longer greasing intervals.
- ▶ Good extreme-pressure properties provide excellent protection to heavily-loaded parts (bearings, etc.).
- ▶ High dropping point (180°C) for increased resistance on parts subjected to high temperatures.
- ▶ Good protection against wear and rust.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

