



TRF V8

ISO VG 220 chainsaw bar oil

USES

This oil has been **specifically** designed for chainsaws bar and chain. It can also be used for lubricating **machine tool slideways** where ISO VG 220 oil is required.

Our full range of chainsaw oils also includes:

- more or less viscous oils for use under severe service conditions: YACCO TRF V8 ISO VG 150 and YACCO TRF V12 ISO VG 320.

- YACCO TRF BIO ISO VG 150 biodegradable oil for maximum protection of the environment and environmentally sensitive areas.



MAIN PHYSICAL DATA

		Methods	Units	TRF V8
Density at	20°C	ASTM D4052	kg/m ³	860
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	219
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	30
Viscosity index		ASTM D2270		178
Pour point		ASTM D97	°C	-30
Cleveland Open Cup Flash Point		ASTM D92	°C	206
Appearance				Ropy
Colour				Green

The data given in this table represents typical production values and should not be taken as specifications.



PROPERTIES & ADVANTAGES

- ▶ Prevents metal-to-metal contact due to its highly adhesive consistency that leaves a long-lasting oil film on the surface of metal parts.
- ▶ Prevents excessive throw-off.
- ▶ Excellent anti-wear properties.
- ▶ ISO VG 220 viscosity exceeding that of most available products. Suitable for very severe service conditions and/or for professional use.

facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

