



LR - 12

Coolant for use in hot climates (-12°C)

USES

Made using monoethylene glycol, demineralised water and specific additives, this premixed coolant does not have to be mixed with water.

Specifically formulated for use in hot climates.



MAIN PHYSICAL DATA

	Methods	Units	Values
Appearance	Visual		Limpid
Colour	Visual		green
Density at 20°C	ASTM D4052	kg/m ³	1038
Protection	ASTM D1177	°C	-12
pH	ASTM D1287		9.4
Reserve of alkalinity (pH 5.5)	ASTM D1121	ml	14

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ The concentration has more inhibitors to provide better protection against corrosion and rust, than using water or a low protection coolant (-5°C for example)
- ▶ Good anti-foam properties.
- ▶ Improves heat dissipation and helps engine cooling.
- ▶ Prevents the formation of deposits in the cooling system
- ▶ Meets the requirements of ASTM D3306 & NFR 15601 standards (except in terms of pH).
- ▶ Frost protection up to -12°C.

PRECAUTIONS FOR USE

- ▶ Can only be mixed with coolants of the same type.
- ▶ Do not use when the outside temperature is below -10°C. Where this is not the case, please contact us so we can advise you on the best product to use.
- ▶ Harmful if ingested. Contains a bittering agent, in accordance with French Decree No. 95-326 of 20th March 1995.



 facebook.com/yaccos

 twitter.com/yaccos

 youtube.com

