



# GREASE GAPL 00

Special grease for central lubrication systems

## USES

Extreme pressure and anti-wear grease recommended for the lubrication of mechanisms exposed to very severe conditions. Particularly suitable for the central lubrication systems of vehicles (lorries, and heavy-duty construction and agricultural equipment).

Can be used where a thin grease (NLGI 00) is required. Effective between -20°C and +140°C.

### Specifications:

NLGI grade 00  
ISO 6743-9 ISO-L-XBDHB 00  
DIN 51825: KPF00N-20  
DIN 51826: G00N-20



## MAIN PHYSICAL DATA

	Method	Units	Values
Colour	Visual		Amber
Appearance	Visual		Smooth
Consistency	ASTM D217	0,1 mm	415
Drop point	ISO 22286	°C	190°C
Base oil viscosity	ASTL D445	mm <sup>2</sup> /s	125
Welding load	ASTM D2596	Kgf	315
Thickener			Lithium

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Lithium grease with enhanced anti-wear and extreme-pressure properties.
- ▶ High resistance to water washout provides excellent anti-rust performance.
- ▶ Good mechanical stability for improved shock resistance.
- ▶ Effective in a wide range of temperatures

