



# ANTIFUITE MOTEUR

Engine stop leak

## USES

Prevents and stops oil leaks without demounting the engine. Suitable for all gasoline and diesel engines, especially in fairly used vehicles or with excessive oil consumption.

**YACCO Engine stop leak** is compatible with all mineral and synthetic 4-stroke engine oils. Recommended for older vehicles or those being more than 5 years old with high mileage.

**CAUTION:** DO NOT USE in engines featuring an internal oil-bath timing belt

## MAIN PHYSICAL DATA

	Method	Units	Values
Aspect	Visual		Liquid
Colour	Visual		Brown
Density at 20°C	ASTM D4052	kg/m <sup>3</sup>	883
Density at 100°C	ASTM D445	mm <sup>2</sup> /s	15.3

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Restores the elasticity of rubber and neoprene oil seal rings and O-rings.
- ▶ Specific additives and a viscosity index improver increase the oil viscosity close to its original SAE grade, mainly under high temperature, thus preventing leaks and drips.
- ▶ Helps to protect the engine. Reduces wear, oil consumption and exhaust smoke.
- ▶ Improves or restores the cylinders compression
- ▶ Developed for cars, this additive is also suitable for all 4-stroke engines. **Do not exceed** the recommended ratio up to 5%.

## INSTRUCTIONS FOR USE

Let the engine reach running temperature, and pour the product into the oil filler port. Make sure that the maximum level has not been exceeded. Adjust if necessary.

One bottle (250 ml) will treat up to 5 litres of oil.

Use **YACCO Engine stop leak** with every oil change.

If your engine is very dirty, we recommend to flush the engine using YACCO Optimizer vidange.

# YACCO LINE



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

