



BVX 500 X – SAE 75W-80

Synthetic high performance transmission oil

USES

Multipurpose transmission oil suitable for all manual transmissions in light vehicles and certain types of commercial vans.

BVX 500 X 75W80 covers a wide range of uses and specifications. It is suitable for use in manual transmissions from a large number of car brands.

Specifications:

API GL-4;

BMW MTF LT-2/ MTF LT-3; GM 1940182 / 1940764 / 1940768;

Fiat 9.55550-MZ9/-MZ10/-MZ12; Honda MTF/MTF-II/MTF-III; Nissan MT-XZ;

Nissan MT-XZ TL/JR Type; MB 235.10; MTF 94; PSA B71 2330;

Volvo 97308 / 97309; VW G 009 317 / VW G 060 726;

Renault Tranself NFJ/NFP/TRJ/TRZ

MAIN PHYSICAL DATA

		Methods	Units	75W-80
Density at	20°C	ASTM D4052	kg/m ³	860
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	59
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	10.2
Viscosity index		ASTM D2270		162
Pour point		ASTM D97	°C	-45
Cleveland Open Cup Flash Point		ASTM D92	°C	200

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Synthetic-based formula provides increased protection for components.
- ▶ Extreme-pressure and anti-wear properties ensure optimal gear protection under the most severe service conditions.
- ▶ Very good compatibility with elastomers.
- ▶ Excellent synchromesh operation over the entire service life of the gearbox.
- ▶ Outstanding anti-foam and filterability properties provide effective lubrication under all conditions.
- ▶ Increased anti-rust and anti-corrosion protection.
- ▶ Suitable for the transmissions of many different European and Asian vehicles.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

