



BVX FE – SAE 75W

High performance fuel economy transmission oil

USES

Universal fuel economy transmission oil suitable for a wide range of passenger cars and light commercial vehicles.

Low viscosity grade SAE 75-W helps to improve fuel economy.

Specifications:

API GL-5 & API GL-4

VW 052 178 / VW 052512 / VW 052726 / VW 052 527

VW 070 726 / VW 060 726

Fiat 9.55550-MZ6/-DA11, Ford WSS-M2C200-D2, Nissan LV MT1 75W

BMW 83 22 2 409 710/83 22 0 397 244 / 83 22 0 306 816

BMW DTF1 (83 22 2 409 710)

MAIN PHYSICAL DATA

		Methods	Units	75-W
Density at	20°C	ASTM D4052	kg/m ³	872
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	28.3
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	5.2
Viscosity index		ASTM D2270		115
Pour point		ASTM D97	°C	-45
Cleveland Open Cup Flash Point		ASTM D92	°C	185

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

► Makes gear changes smoother upon start-up and helps to protect the environment by reducing fuel consumption and exhaust emissions (CO₂, etc.).

► High extreme-pressure properties provide excellent resistance to heavy loads, even under the most severe operating conditions.

► Compatible with gear materials and seals.

► Excellent anti-foam, anti-corrosion and anti-wear properties mean enhanced protection of gear components under any service conditions.

► This oil has a wide range of uses and is recommended for many recent European and Asian conventional manual transmissions.



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

