



AGRIPRO UTO 10W-30

Fluid for transmissions and hydraulic systems

USES

Lubrication of transmissions equipped with wet disc brakes system on agricultural and construction equipment where the use of API GL-4 SAE 10W- 30 or SAE 80W is specified.

Also suitable for automatic or hydrostatic transmissions, torque convertors, hydraulic systems, power steering, power take-off (PTO) with oil-immersed clutch where the manufacturer recommend the use of UTTO (Universal Tractor transmission Oil) oi meeting one of the following specifications:

Specifications:

API GL-4; Allison C4; ISO HV 68;
AGCO Massey Ferguson CMS M1143/ M1135/ M1129A;
Fiat New-Holland FNHA-2-C-201.00; Ford M2C134D/ 86B/ 53A;
John Deere JDM J20C/ J20A; Caterpillar TO-2;
Case IH MS 1206/ 1205; Landini UTTO; Same Deutz Fahr UTTO; Fendt



MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m ³	887
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	69
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	10.5
Viscosity index		ASTM D2270		149
Pour point		ASTM D97	°C	-41
Cleveland Open Cup Flash Point		ASTM D92	°C	220

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Excellent anti-wear and extreme-pressure properties.
- ▶ Good protection against rust and corrosion.
- ▶ Specific friction coefficient suitable for clutch and wet brakes transmissions.
- ▶ Excellent oxidation and shear resistance.
- ▶ Outstanding anti-foam properties.
- ▶ Very good stability in service.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

