



MULTIP XTRA 2

Extreme-pressure lithium/calcium grease

USES

Extreme-pressure adhesive, water-insoluble grease. Recommended for ball bearings, joints and various types of mechanisms. Particularly suitable for use in conditions involving heavy loads and high temperatures. Also suitable for use in the presence of water and dust.

It can be used in cars, motorcycles, marine, agricultural and construction equipment, industrial and off-road vehicles, etc.

Specifications:

NLGI grade 2

ISO 6743-9 : ISO L-XBDHB 2

DIN 51502 : KP 2 N-20

Range of temperature: -20°C/+140°C



MAIN PHYSICAL DATA

	Grade NLGI 2
Colour	Green
Drop point	>180°C
Thickener	Lithium/calcium
Weld load	315kg
Base oil viscosity at 40°C	310mm ² /s

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Insoluble in water (even boiling water) and steam. Recommended for equipment used outdoors or in the presence of water or mud.
- ▶ Excellent adhesion, meaning long-lasting lubrication.
- ▶ Outstanding extreme-pressure properties for conditions involving heavy loads.
- ▶ Good anti-wear and anti-rust protection.
- ▶ Drop point at 180°C provides increased protection for parts which tend to overheat.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

