



GRAISSE MULTIP EP 0

Multipurpose grease

USES

Suitable for low-pressure centralised systems and use in low temperatures. Can also be used with certain types of industrial gear cases.

Ideal for lubricating machine tools used with building materials. Specifically designed for bearings and couplings working under very severe service conditions

Specifications:

NLGI grade 0
ISO L-XBDHB 0
DIN KP0N-20 / MP0N-20

MAIN PHYSICAL DATA

| | NLGI grade 0 |
|--------------|------------------------------|
| Colour | Amber |
| Appearance | Semi-fluid |
| Consistency | 355-385 (10 ⁻⁴ m) |
| Drop point | 180°C |
| Thickener | Lithium |
| Welding load | >= 315kg |

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Good anti-wear, extreme-pressure and anti-rust properties.
- ▶ Very low solubility in water.
- ▶ Excellent adhesion and mechanical stability
- ▶ Almost fluid consistency for easier spreading of the grease in the system.
- ▶ Suitable for use in certain types of gears under housing, when the manufacturer recommends a grease of this consistency (rotary harrows, etc.).
- ▶ Temperature range : -20°C / + 140°C, peak up to 170°C.

