



FUEL STABILIZER

Fuel additive

USES

YACCO FUEL STABILIZER is an additive to be added to the tank to preserve and stabilize the fuel. It is particularly recommended for the maintenance of seasonal use vehicles : it protects the engine and fuel during long period of storage.

Applications : boats, agriculture, car engines, motorbikes, classic cars, quads, snowmobiles, etc. .

MAIN PHYSICAL DATA

	Methods	Units	Values
Aspect	Visual		Limpid
Colour	Visual		Red
Density at 20°C	ASTM D4052	kg/m3	830

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Prevents corrosion
- ▶ Stalilizes the fuel and prevents the formation of deposits in the combustion chamber
- ▶ Preserves the fuel in the tank
- ▶ Developed for gasoline engines running on E10, E5, SP98 E5 fuels. Also compatible with diesel engines, in particular those running on biodiesel (B7 diesel, off-road diesel...)

DIRECTIONS

- Add 10 ml per 2 litres of fuel
- Measure the desired quantity of additive in the graduated measuring cup by pressing at the base of the bottle.
- pour the dose into the fuel tank before refueling

PRECAUTION FOR USE

Depending on time and storage conditions, sedimentation may occur in the product. This is a reversible reaction. Shake the bottle before use, in order to to restore product's characteristics

Before using this product, read the instructions on the label and consult the safety data sheet at yacco.com

